

# SOL'S ODYSSEY

UNISEX RECYCLED T-SHIRT

SOL'S®  
the fair spirit

03805



## Jersey 170

Ribbed round neck

Neck tape

Short sleeves

Cut and sewn

## Composition

55% recycled cotton - 45% recycled polyester

## Interview



## A committed product



## Colors available



Recycled black Recycled white Recycled navy

## Sizes available



Sizes	XS	S	M	L	XL	XXL	3XL	4XL
A/B	67/46	70/48	72/51	74/54	76/57	78/60	80/63	82/66

\*Size available on some colors

## Packaging

Box size: **54 x 38 x 18 cm**

Weight per box: **9,8 kg**



50



50

## Personalization

• **Embroidery** : This technique is generally used for personalisations that aim for a high-end finish. This technique is the most resistant to washing and use. The embroidery can be applied directly to the product or through embroidered patches. It can be done with thickness effects (with foam) or through patches that will then be affixed to the final product, allowing for variations in materials.

• **Transfer** : The right technique for all materials. It is recommended for luggage, heavy garments, difficult to access surfaces. It consists of transferring the marking from a paper support to the garment by hot gluing. The marking by gluing brings rigidity to light supports at the level of the marking zone, nevertheless, the product keeps all its qualities of comfort.

• **Digital Printing** : The printing method that knows no limits: precision, colour effects, number of colours... This technique can be used to mark all types of product quantities and is particularly suitable for cotton-based materials.

• **Screen Printing** : The most widely used technique. It consists, by the stencil method, of depositing the ink directly on the product. There are as many screens and passages as there are colours in the motif to be reproduced and all colours can be achieved. This technique makes it possible to produce very large quantities. It allows the use of inks with various effects for very different renderings and is adapted to almost all textile supports. The marking of coloured substrates requires an opacifying undercoat called « background white ».